



MATERIAL SAFETY DATA SHEET

Date Issued: 12/22/2004
MSDS No: 1621-G/5G/54G
Date Revised: 07/17/2012
Revision No: 5

Ecoline Flux Remover

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Ecoline Flux Remover
PRODUCT DESCRIPTION: Flux Remover
PRODUCT CODE: 1621-CAN/EUR/G/5G/54G
ACTIVE INGREDIENT(S): 2-Propanol; Ethanol

MANUFACTURER

Techspray, L.P.
 1001 N.W. 1st Street
 P.O. Box 949
 Amarillo, TX 79107
Emergency Contact: Chemtrec
Emergency Phone: 1-800-858-4043
Service Number: 1-800-858-4043

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC CCN#21858 (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666
Emergency Phone :(800) 858 - 4043

2. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

"F" - Highly flammable
 R11 - Highly flammable.
 "Xn" - Harmful
 R20/22 - Harmful by inhalation and if swallowed.
 R36/37/38 - Irritating to eyes, respiratory system and skin.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Transparent, colorless liquid.

IMMEDIATE CONCERNS: Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract. Causes skin irritation. Harmful if swallowed.

POTENTIAL HEALTH EFFECTS

EYES: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

SKIN: Prolonged or repeated skin contact may cause irritation.

INGESTION: Ingestion of large amounts may produce abdominal pain, nausea and vomiting. Swallowing small amounts is not likely to produce harmful effects.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Liquid splashed in the eye may cause redness, irritation and conjunctivitis.

SKIN: Prolonged or exposure may cause skin irritation.

INGESTION: For large amounts; abdominal pain, nausea and vomiting.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

ACUTE TOXICITY: Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result.

TARGET ORGAN STATEMENT: Prolonged or repeated overexposure may cause central nervous system, kidney, liver, and lung damage.

MATERIAL SAFETY DATA SHEET



Date Issued: 12/22/2004
MSDS No: 1621-G/5G/54G
Date Revised: 07/17/2012
Revision No: 5

Ecoline Flux Remover

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS	EINECS
2-Propanol	8 - 14	67-63-0	200-661-7
Ethanol	18 - 25	64-17-5	200-578-6
n-Propyl acetate	1 - 3	109-60-4	2036861
n-Heptane	50 - 70	142-82-5	

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Aspiration hazard. If swallowed, vomiting may occur spontaneously, but do not induce. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Call a physician immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (22°F) TAG CC

GENERAL HAZARD: Vapors can travel to a source of ignition and flash back.

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes and oxides of carbon.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain spill with dike to prevent entry into sewers.

LARGE SPILL: Clean up spills immediately, observing precautions in Protective Equipment section.

GENERAL PROCEDURES: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth, gravel, etc. as necessary and place in closed containers for disposal.

SPECIAL PROTECTIVE EQUIPMENT: Only personnel equipped with proper respiratory and skin/eye protection should be permitted in area. See Section 8 for details.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Wash thoroughly after handling. Use only in a well ventilated area. Store in a cool dry place.



MATERIAL SAFETY DATA SHEET

Date Issued: 12/22/2004
MSDS No: 1621-G/5G/54G
Date Revised: 07/17/2012
Revision No: 5

Ecoline Flux Remover

HANDLING: Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and prolonged skin exposure. Do not allow product to contact open flame or electrical heating elements because dangerous decomposition products may form.

STORAGE: Store away from heat.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
2-Propanol	TWA	400 ppm	980 mg/m ³	400 ppm	983 mg/m ³	NL [1]	NL [1]
	STEL	500 ppm	1225 mg/m ³	500 ppm	1230 mg/m ³	NL	NL
Ethanol	TWA	1000 ppm	1900 mg/m ³	1000 ppm	1880 mg/m ³	NL	NL
	STEL	NL ppm	NL mg/m ³	NL ppm	NL mg/m ³	NL	NL
n-Propyl acetate	TWA		200 ppm		200 ppm		
	STEL		250 ppm		250 ppm		
n-Heptane	TWA	400 ppm	1600 mg/m ³	400 ppm			
	STEL	500 ppm	2000 mg/m ³	500 ppm			

OSHA TABLE COMMENTS:
1. NL = Not Listed

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Viton, Solvex, Butyl, Buna, Neoprene.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances

MATERIAL SAFETY DATA SHEET



Date Issued: 12/22/2004
MSDS No: 1621-G/5G/54G
Date Revised: 07/17/2012
Revision No: 5

Ecoline Flux Remover

where air purifying respirators may not provide adequate protection.

WORK HYGIENIC PRACTICES: Wash hands before eating and wash before reuse.

OTHER USE PRECAUTIONS: Emergency shower and eyewash facility should be in close proximity.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Boiling Point (°C)	Specific Gravity
2-Propanol	11.7	82.4	0.785

ODOR: Characteristic odor.

APPEARANCE: Clear, Colorless liquid

PERCENT VOLATILE: 100 at 20°C (68°F)

VAPOR DENSITY: 2.1 (Air=1)

FLASHPOINT AND METHOD: (22°F) TAG CC

SOLUBILITY IN WATER: Moderate

SPECIFIC GRAVITY: 0.710 (water=1)

(VOC): 713.400 g/L (non-exempt VOC)

10. STABILITY AND REACTIVITY

STABILITY: Stable.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Stable. However, may decompose if heated.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon (CO and CO₂) may form when heated to decomposition.

INCOMPATIBLE MATERIALS: Incompatible with alkali or alkaline earth metals - powdered Al, Zn, Be, etc.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
n-Propyl acetate	9370 mg/kg	> 20 ml/kg	8000 ppm

DERMAL LD₅₀: Slight to very low toxicity.

ORAL LD₅₀: Oral - Rat LD₅₀:5045 mg/kg for 2-propanol.

INHALATION LC₅₀: Slight to very low toxicity.

EYE EFFECTS: Mixture is a moderate eye irritant.

SKIN EFFECTS: Prolonged exposure may cause irritation and defatting of skin.

CARCINOGENICITY

MATERIAL SAFETY DATA SHEET



Date Issued: 12/22/2004
MSDS No: 1621-G/5G/54G
Date Revised: 07/17/2012
Revision No: 5

Ecoline Flux Remover

Chemical Name	NTP Status	IARC Status	OSHA Status
2-Propanol	NOT LISTED	NOT LISTED	NOT LISTED
Ethanol	NOT LISTED	NOT LISTED	NOT LISTED
n-Propyl acetate	NOT LISTED	NOT LISTED	NOT LISTED

IARC: NOT listed

NTP: NA = Not Applicable

OSHA: NOT listed

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial species. Due care should be taken to avoid the accidental release of this material into the environment.

ECOTOXICOLOGICAL INFORMATION: Invertebrate toxicity: LC50 (30 min) Photobacterium phosphoreum = 1540 ppm Microtoxicity test.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Federal, State, and Local laws governing disposal of materials can differ. Ensure compliance with proper authorities before disposal.

FOR LARGE SPILLS: Contaminated sawdust, vermiculite, or porous surfaces must be disposed of in a permitted hazardous waste management facility. Recovered liquids may be reprocessed or incinerated or must be treated in a permitted hazardous waste management facility.

GENERAL COMMENTS: Dispose of in a manner consistent with federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Flammable Liquids, N.O.S. (Heptane, Ethanol)

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: 1993

PACKING GROUP: II

ROAD AND RAIL (ADR/RID)

KEMLER NUMBER: UN1993

HAZARD CLASS: 3

AIR (ICAO/IATA)

SHIPPING NAME: Flammable Liquids, N.O.S. (Heptane, Ethanol)

UN/NA NUMBER: 1993

PRIMARY HAZARD CLASS/DIVISION: 3

MATERIAL SAFETY DATA SHEET



Date Issued: 12/22/2004
MSDS No: 1621-G/5G/54G
Date Revised: 07/17/2012
Revision No: 5

Ecoline Flux Remover

PACKING GROUP: II

NOTE: Domestic shipments only. When shipping International contact TechSpray shipping department.

VESSEL (IMO/IMDG)

SHIPPING NAME: Flammable Liquids, N.O.S. (Heptane, Ethanol)

UN/NA NUMBER: 1993

PRIMARY HAZARD CLASS/DIVISION: 3

PACKING GROUP: II

NOTE: Page 3232

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: IMMEDIATE / DELAYED

313 REPORTABLE INGREDIENTS: 2-propanol (CAS #67-63-0)

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
2-Propanol	8 - 14	67-63-0

TITLE III NOTES: Not listed as an Extremely Hazardous Substance.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2-Propanol	67-63-0
Ethanol	64-17-5
n-Propyl acetate	109-60-4

TSCA REGULATORY: This product is listed on the TSCA Inventory.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

CALIFORNIA PROPOSITION 65: This product does not contain any chemicals known to the State of California to cause cancer.

RCRA STATUS: D001

OSHA HAZARD COMM. RULE: Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

WHMIS CLASS: Class B2 - Flammable Liquids. Class D2B - Toxic Materials.

CANADA INGREDIENT DISCLOSURE LIST: CAS# 67-63-0 is listed on Canada's Ingredient Disclosure List.

EUROPEAN COMMUNITY

MATERIAL SAFETY DATA SHEET



Date Issued: 12/22/2004
MSDS No: 1621-G/5G/54G
Date Revised: 07/17/2012
Revision No: 5

Ecoline Flux Remover

EEC LABEL SYMBOL AND CLASSIFICATION



"F" - Highly flammable
 R11 - Highly flammable.



"Xn" - Harmful
 R20/22 - Harmful by inhalation and if swallowed.

R36/37/38 - Irritating to eyes, respiratory system and skin.

16. OTHER INFORMATION


APPROVED BY: Pierce A. Pillon **TITLE:** Chemist

REVISION SUMMARY: This MSDS replaces the 03/02/2012 MSDS. Revised: **Section 2:** TERATOGENIC EFFECTS. **Section 3:** Wt.%. **Section 11:** SKIN EFFECTS, TERATOGENIC EFFECTS. **Section 15:** CERCLA REGULATORY, CERCLA RQ, 302/304 EMERGENCY PLANNING, 40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION.

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	3
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



DATA SOURCES: Code of Federal Regulations (CFR) The Sigma-Aldrich Library of Regulatory and Safety Data
 OSHA Hazard Communication Standard (29CFR1910.1200) Various Federal, State and Local Regulations

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither Tech Spray, L.P., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.