SAFETY DATA SHEET



G3 Blue Shower® Maintenance Cleaner

Section 1. Identifi	cation
Product identifier	: G3 Blue Shower® Maintenance Cleaner
Product code	: 1630-16S
Other means of identification	: 1630-16S (23001) Industrial/Professional use Date of commencement of manufacture or import January 01, 2023
Product type	: Aerosol.
Relevant identified uses of t	the substance or mixture and uses advised against
Identified uses	
Not applicable.	
Uses advised against Not applicable.	
Supplier's details	: Manufacturer Techspray 8125 Cobb Center Drive Kennesaw, GA 30152 Tel: 678-819-1408 Toll free: 1-800-858-4043 Fax: 1 806-372-8750
	Distributor EMX Enterprises LTD 250 Granton Drive Richmond Hill, ONT Canada L4B 1H7 905-764-0040
Emergency telephone number (with hours of operation)	: Chemtrec - 1-800-424-9300 CANUTEC (Canadian Transportation): (613) 996-6666 Emergency phone: (800) 858-4043 24/7
Section 2. Hazard	identification
Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION - Category 1 GASES UNDER PRESSURE Compressed gas
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.
	May damage fertility or the unborn child. Contains gas under pressure. May explode when heated.

Section 2. Hazard identification

Prevention	: Wear protective gloves. Wear eye or face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	 IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Percentage of the mixture consisting of ingredient(s) of unknown acute oral toxicity: 37%

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Cleaner.
identification	Industrial/Professional use
	Date of commencement of manufacture or import January 01, 2023

Ingredient name	Synonyms	% (w/w)	CAS number
trans-1,2-Dichloroethylene	Ethene, 1,2-dichloro-, (1E)-; Ethene, 1,2-dichloro-, (E)-; Ethylene, 1,2-dichloro-, (E)-; DICHLOROETHYLENE-TRANS; ETHENE, 1,2-DICHLORO- (E); 1,2-DICHLOROETHYLENE; 1,2-trans-Dichloroethylene; ETHENE, TRANS-1,2-DICHLORO-; Dichloroethylene; 1,2-Dichloroethylene; (1E) -1,2-Dichloroethene		156-60-5
Ethyl alcohol	ethyl alcohol; ALCOHOL; Ethyl alcohol (Ethanol); EtOH; Grain alcohol; Cologne spirit; undenatured ethyl alcohol, of an alcoholic strength by volume of 80 % or more and containing up to 20 % activated carbon; mixture, consisting of ethyl alcohol, isopropanol, n-propanol and small quantities of other organic products; Denatured Alcohol; METHYLCARBINOL; 1-HYDROXYETHANE	≥1 - ≤5	64-17-5

Ranges if listed above for hazardous ingredient(s) are prescribed ranges. The actual concentration(s) or actual concentration range(s) are being withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effect			
Eye contact		Causes serious eye irritation.	
Inhalation		Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.	
Skin contact	:	Causes skin irritation.	
Ingestion	:	Harmful if swallowed.	
Over-exposure signs/symp	oton	<u>ns</u>	
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	:	Adverse symptoms may include the following: irritation redness	
Ingestion	:	No specific data.	
Indication of immediate med	<u>dica</u>	l attention and special treatment needed, if necessary	
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	
Specific treatments	:	No specific treatment.	
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

<u>Extinguishing media</u>	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. Bursting aerosol containers may be propelled from a fire at high speed.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for co	nt	ainment and cleaning up	
Small spill		Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits		
trans-1,2-Dichloroethylene	 CA British Columbia Provincial (Canada, 1/2020). TWA: 200 ppm 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 793 mg/m³ 8 hours. TWAEV: 200 ppm 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 200 ppm 8 hours. 8 hrs OEL: 793 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 250 ppm 15 minutes. TWA: 200 ppm 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 200 ppm 8 hours. 		
Ethyl alcohol	 CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1880 mg/m³ 8 hours. 8 hrs OEL: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 6/2021). STEL: 1000 ppm 15 minutes. CA Ontario Provincial (Canada, 6/2019). STEL: 1000 ppm 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 6/2021). STEV: 1000 ppm 15 minutes. 		

Biological exposure indices

No exposure indices known.

Section 8. Exposure controls/personal protection

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ires</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Appearance	
Physical state	: Liquid. [Aerosol.]
Color	: Clear. Colorless.
Odor	: Ethereal. [Slight]
Odor threshold	: Not available.
рН	Not available.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: Not available.
Flash point	: Not applicable.
Evaporation rate	: >1 (butyl acetate = 1)
Flammability	: Not available.
Date of issue/Date of revision	: 12/14/2022 Date of previous issue

Section 9. Physical and chemical properties and safety characteristics

Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	: 122.7 kPa (920.45 mm Hg)
Relative vapor density	: Not available.
Relative density	: 1.229
Solubility in water	: Not available.
Partition coefficient: n- octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Heat of combustion	: 0.84 kJ/g
Viscosity	: Not available.
Particle characteristics	
Median particle size	: Not applicable.
Aerosol product	
Type of aerosol	: Spray
Ignition distance	: 0 cm
Enclosed space ignition - Time equivalent	: 545 s/m³
Enclosed space ignition -	: 2010 g/m³

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Deflagration density

Product/ingredient name	Result	Species	Dose	Exposure
trans-1,2-Dichloroethylene	LC50 Inhalation Gas.	Rat	24100 ppm	4 hours
-	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	1235 mg/kg	-
Ethyl alcohol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
trans-1,2-Dichloroethylene	Eyes - Moderate irritant	Rabbit	-	10 mg	-
· · · · · ·	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				mg	
Ethyl alcohol	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	0.066666667	-
				minutes 100	
				mg	
	Eyes - Moderate irritant	Rabbit	-	100 uL	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure	lot available.	
Potential acute health effect		
Eye contact	Causes serious eye irritation.	
Inhalation	xposure to decomposition products may cause a health hazard. Serious nay be delayed following exposure.	effects
Skin contact	Causes skin irritation.	
Ingestion	łarmful if swallowed.	
Symptoms related to the ph	, chemical and toxicological characteristics	
Eye contact	dverse symptoms may include the following: ain or irritation /atering edness	
Inhalation	dverse symptoms may include the following:	

Inhalation : Adverse symptoms may include the following: respiratory tract irritation coughing

Section 11. Toxicological information

	5	
Skin contact	Adverse symptoms may include the following: irritation redness	
Ingestion	No specific data.	
Delayed and immediate effe	and also chronic effects from short and long term exposu	re
<u>Short term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health ef	<u>></u>	
Not available.		
General	No known significant effects or critical hazards.	
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	
Reproductive toxicity	No known significant effects or critical hazards.	

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
trans-1,2-Dichloroethylene	1235	N/A	N/A	N/A	N/A
Ethyl alcohol	7000	N/A		124.7	N/A
Methyl alcohol	100	15800		N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
trans-1,2-Dichloroethylene	Acute LC50 220000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
Ethyl alcohol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
-	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia	48 hours
	Acute LC50 42000 µg/l Fresh water	franciscana - Larvae Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks

Persistence and degradability

Not available.

Bioaccumulative potential

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
trans-1,2-Dichloroethylene	2.09	-	low
Ethyl alcohol	-0.35		low

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	TDG Classification	DOT Classification	IMDG	ΙΑΤΑ
UN number	UN1950	UN1950	UN1950	ID8000
UN proper shipping name	AEROSOLS	Aerosols, non- flammable	AEROSOLS IN LIMITED QUANTITIES OF CLASS 2	Consumer commodity ID8000
Transport hazard class(es)	2.2	2.2	2.2	9
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

TDG Classification	:	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).
DOT Classification	:	Reportable quantity 2222.2 lbs / 1008.9 kg [216.86 gal / 820.9 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

Section 15. Regulatory information

-				
Canadian lists				
Canadian NPRI	: The following components are listed: volatile organic compounds; volatile organic compounds; ethanol			
CEPA Toxic substances	 The following components are listed: hydrofluorocarbons; hydrofluorocarbons; carbon dioxide 			
International regulations				
Chemical Weapon Convent	ion List Schedules I, II & III Chemicals			
Not listed.				
Montreal Protocol				
Ingredient name		Status		
HFC-134a		Annex F, Group I		
HFC-245fa		Annex F, Group I		
Stockholm Convention on F	Persistent Organic Pollutants			
Not listed.				
Rotterdam Convention on F	Prior Informed Consent (PIC)			
Not listed.				
UNECE Aarhus Protocol on	POPs and Heavy Metals			
Not listed.	<u>· · · · · · · · · · · · · · · · · · · </u>			
Inventory list				
Australia	: All components are listed or exempted.			
Canada	: All components are listed or exempted.			
China	: All components are listed or exempted.			
Eurasian Economic Union	: Russian Federation inventory: Not determined.			
Japan	: Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.			
New Zealand	: All components are listed or exempted.			
Philippines	: All components are listed or exempted.			
Republic of Korea	: All components are listed or exempted.			
Taiwan	: All components are listed or exempted.			
Thailand	: Not determined.			
Turkey	: Not determined.			
United States	: All components are active or exempted.			
Viet Nam	: All components are listed or exempted.			
Section 16 Other	information			

Section 16. Other information

<u>History</u>	
Date of printing	: 12/14/2022
Date of issue/Date of revision	: 12/14/2022
Date of previous issue	: 12/14/2022
Version	: 3
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HPR = Hazardous Products Regulations IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships,

Date of issue/Date of revision	: 12/14/2022	Date of previous issue	: 12/14/2022	Version : 3	11/12

Section 16. Other information

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
	Calculation method Calculation method Calculation method

References

: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.