



## Wondermask WSOL Washable Solder Mask

Product# 2204

### Product Description

Ideal water washable mask for closed loop systems. Quickly and easily removed with inline and batch cleaning system.

Techspray's WonderMASK is the industry-leading temporary solder mask brand because of quality and versatility. Depending on the product, mask can be peeled off manually or washed off in a batch or inline system.

WonderMASK WSOL has a number of useful applications in PCB assembly:

- Thru-hole masking – Prevent soldering open holes in a wave soldering process by covering with WonderMASK. All of the masks listed below are well suited for this application.
- Temporary component adhesive – WonderMASK can be used to tack down components on double-sided PCBs.

All Techspray WonderMASK products have the following advantages:


- Can be cured in pre-heat
- Withstands lead-free soldering temperatures up to 640°F (343°C) in wave soldering process
- RoHS compliant

### Features / Benefits

- 100% water-soluble
- Safe on ion beds & filters in closed-loop cleaning systems
- Non-corrosive
- Low odor

### Usage Instructions

Apply a 5 to 30 mil coating to desired area. The substrate should be free from grease, oil, and particulate matter. Drying times depend upon ambient humidity. Under normal conditions **WonderMASK® Wsol** will cure in 30 minutes at 65°C/149°F. Do not over cure, as blistering of mask can occur.



### Typical Product Data and Physical Properties

<b>Physical state:</b>	Liquid
<b>Flash point:</b>	Closed cup: 55.4°F (13°C)
<b>Flammable limits:</b>	Lower: 7.3% Upper: 36%
<b>Color:</b>	Pink red
<b>Odor:</b>	Alcohol-like
<b>Shelf life:</b>	2 years

### Performance & Application Data

Application	Hand, Pneumatic
Viscosity	11,500-15,500 cps
Suggested thickness	5-30 mils
Thinner	Methanol
Cure time	30 min. @65°C
Removal	Soluble in Water 49 °C or higher

## Wondermask WSOL Washable Solder Mask

Product# 2204

### Packaging and Availability

2204-8SQ	8 Ounce Liquid
2204-G	1 Gallon Liquid

### Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

### Resources

Techspray® products are supported by global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.